



Product specification sheet



- **Profile type:**

370



- **Description:** Edge trim aluminium, adaptable
- **Application:** as edge for bonded resilient floors and carpets
- **Countersunk drilled:** countersunk drilled for 3,0 mm screw heads
- **Length of the profile:** 0.9m, 1.0m, 2.70m
- **Width of the profile:** 26 mm
- **Visible part on top:** 12.0 mm
- **Gauge of the profile:** 8.5 mm
- **Additional versions:** 370 SK (self-adhesive)
- **Alloy of the profile:** AlMgSi0,5F22
- **Anodized colours:** **F4** silver, **F5** gold, **F9** sand, **F6** bronze, **F2G** stainless steel optic
- **Additional colours:** **F3** aluminium polished
- **Installation:** fastening with screws and dowels (plugs) or gluing with suitable adhesives



The indicated data are typical or average values, but are not assured attributes. This product is not subject to the Construction Products Regulation.

Product specification sheet



It is typically used to join flooring material such as carpet, carpet tile, traditional carpet with underlay and resilient or hard flooring.

The design of the profile allows the edge of the carpet to be secured and concealed, thus providing a neat finish and protecting the raw edge of the carpet.



The carpet is fitted into the profile and then the top is flattened into the carpet pile to provide a secure fit. It is recommended that the carpet is sealed to reduce the risk of fraying before the profile is flattened down. 370 is available as well with carpet gripper under reference **370 T**.

Product specification sheet



- **Profile type:**

370 SK



- **Description:** Edge trim aluminium, adaptable, self-adhesive
- **Application:** Enclosing floor coverings in privately used Living area, only partially suitable for wheels and wheels
Please note: Miter changes the cut angles!
- **Length of the profile:** 0.9m, 1.0m, 2.70m
- **Width of the profile:** 26 mm
- **Visible part on top:** 12.0 mm
- **Gauge of the profile:** 8.5 mm
- **Alloy of the profile:** AlMgSi0,5F22 (EN AW-6060)
- **Anodized colours:** **F4** silver, **F5** gold, **F9** sand, **F6** bronze, **F2G** stainless steel optic
- **Additional colours:** **F3** aluminium polished
- **Installation:** fastening with screws and dowels (plugs) or gluing with suitable adhesives



The indicated data are typical or average values, but are not assured attributes. This product is not subject to the Construction Products Regulation.