

WP COMFORT PLANK

3-layer Overall thickness 11 mm with 2,5 mm wear layer

INSTALLATION TECHNIQUES:

Dimensions: 1800 x 175 x 11 mm

Functionalities:



MAINTENANCE-FREE PARQUET: No maintenance required for ProStrong and ProActive+ surfaces in residential use.



HEALTHY PARQUET: Room climate control and allergy-friendly, antibacterial, breathable and antistatic properties.



SOUND-REDUCTION PARQUET: With full-surface bonding, excellent room sound insulation



Product description:

Production site:	Austria	Wood species/colors
Total thickness	11 mm	Gratings/additional treatments:
Wear layer	2,5 mm solid wood	See current price list
Bottom layer material	Spruce with vertically arranged growth rings	
Backing	Spruce	
Processing	Longitudinal connection "Double-Click" with a double locking mechanism, frontal lock made of solid wood	
Moisture content	long seasoned and technically dried wood (moisture content 8 % ± 1 %)	
Composition	Approx. 91% renewable raw material wood, 8% of combined water and approx. 1% synthetic material	
Under-floor heating	Oak and Ash ideally suited. Weitzer Parkett recommends complete adhesion	
Fire resistance	C _{fl} – s1 at surface Pro Active+ (hardly inflammable, please pay attention to the conditions for installation), D _{fl} – s1 at surface Pro Vital finish (normal inflammable, please pay attention to the conditions for installation)	
Heat conductivity resistance	0,085 m²K/W	
Renovation	multiple sanding possible	
Degree of hardness according to Brinell	23-42 N/mm²	
Ecological Responsibility		



Surfaces:



PROACTIVE+ – THE NATURAL MATT SURFACE FINISH

Combines the advantages of the ProStrong surface finish with the appearance of the natural Oiled finish ProVital. Meets Class C of ÖNORM C 2354 (the highest standard for anti-scratch and resistance against certain chemicals etc.). Combines antistatic and antibacterial qualities. Meets the requirements of the chair-rollers test according to EN 425. The pendulum value according to ÖNORM EN 13036-4 is 90.



PROVITAL finish – THE NATURAL OILED SURFACE FINISH

Oil from natural, plant-based raw materials and natural resins, sealing the open pores. Extremely breathable. Local renovation is possible. Surface oiled at the end of the workshop production process (finish). For public use, an additional finish application is required after installation. The pendulum value according to ÖNORM EN 13036-4 is 144. Natural coating material according to ÖNORM C 2380.

Intelligent Characteristics:

- Patented double-click system (fast and safe to lay, highest locking force on the market)
- Patented press-stud principle for simultaneous locking of the longitudinal and header joints in one movement
- Fast and simple one-man assembly and disassembly
- Can be completely adhered to the subfloor
- Header joint edge locking mechanism made from spruce wood only – free from plastic components and plasticizers
- Spruce supporting material with vertically arranged growth rings

Concluding remark: Measurements and technical specification of wood may be subject to insignificant technical material and production deviations. PEFC/FSC on request. Latest technical status of December 2017.